



PVC-Gasket, transparent

Hexagon nut G1/2 SW36 with 2x M4 female thread for anti-rotation



Media	MM
 Potable water, hot	02
 Potable water, cold	03
 Spring water	04
 Non-potable water, hot	05
 Non-potable water, cold	06

Max. bench thickness: 50 mm
Bench drilling: $\varnothing 21+1$ mm

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS IN MM

WEIGHT: 1000.38g

	DATE	NAME
CREATED	15.05.2023	C. Vowinkel
CHECKED	15.05.2023	C. Vowinkel
RELEASED	15.05.2023	C. Vowinkel

THIS DRAWING IS PROPERTY OF ILA GMBH, IT CAN NOT BE PUBLISHED OR COMMUNICATED WITHOUT CONSENT OF ILA GMBH

DESCRIPTION
Bench mounted single turret valve for water. Inlet connection: 70mm shank with G1/2 male thread. Height: 300mm. U-Swivel spout with 200mm stand out and removable plastic. hose nozzle Total stand out of 300mm. Molded nylon handle with media indication according to EN13792. Rubber compression control headwork

DRAWING NUMBER.
14.1000.20MM.0300

A3



SCALE: 1:2

PAGE: 1 / 1

INDEX	CHANGE	DATE	NAME